



514, 6th Floor, Adamji Bldg., 413, Narshi Natha Street, Mumbai - 400 009. (INDIA).

Tel. : 0091-22-2343 9093 | Fax : 0091-22-6634 9992 | E-mail : info@hajexports.com | Web : www.hajexports.com

TECHNICAL DATA SHEET

ACRYLIC RESIN - HAJCRYL- 24

HajCRYL-24 IS FREE FLOWING SOFT AND FLEXIBLE ACRYLIC RESIN OF MEDIUM MOL WT. SUITABLE FOR A VARIETY OF HEAT SEAL LACQUER APPLICATION. HAJCRYL-24 IS A BUTYL METHACRYLATE –METHYL METHACRYLATE COPOLYMER .

TYPICAL PROPERTIES:

TYPE	ACRYLIC CO-POLYMER IN BEAD FORM
AVERAGE MOLECULAR WEIGHT	120,000 ± 5000
ACID NO.	0
GLASS TRANSITION TEMPERATURE (TG.)	44°C
VISCOSITY @ 30°C (40% IN TOLUENE)	200 ± 10 SECS.
SOLIDS	> 98%.
SOLUBILITY	IS SOLUBLE IN SOLVENTS LIKE ESTERS, KETONES, HYDROCARBONS AND GLYCOL ETHERS.

HajCRYL-24 IS COMPATIBLE WITH A WIDE RANGE OF RESINS SUCH AS , CHLORINATED RUBBER, VINYL RESINS, NC, CAB, CAP ETC. IT CAN ALSO BE PLASTICIZED BY PHTHALATE, PHOSPHATE OR SEBACATE PLASTICIZER.

COMPLIES WITH FDA 21 CFR 175.300, 21 CFR 176.170, 21 CFR 176.180 & 21 CFR 177.1010.