



514, 6th Floor, Adamji Bldg., 413, Narshi Natha Street, Mumbai - 400 009. (INDIA).

Tel. : 0091-22-2343 9093 | Fax : 0091-22-6634 9992 | E-mail : info@hajexports.com | Web : www.hajexports.com

TECHNICAL DATA SHEET

ACRYLIC RESIN - HAJCRYL- 64

HajCRYL-64 IS FREE FLOWING SOFT AND FLEXIBLE ACRYLIC RESIN OF LOW MOL WT. SUITABLE FOR APPLICATION FOR HEAT SEALING PVC,PVDC,PS. HAJCRYL-64 IS A BUTYL METHACRYLATE –METHYL METHACRYLATE COPOLYMER.

TYPICAL PROPERTIES:

TYPE	ACRYLIC CO-POLYMER IN BEAD FORM
AVERAGE MOLECULAR WEIGHT	60000
ACID No.	3
GLASS TRANSITION TEMPERATURE (TG.)	58°C
VISCOSITY @ 30°C (40% IN TOLUENE)	340 CPS
SOLIDS	> 98%.
SOLUBILITY	IS SOLUBLE IN SOLVENTS LIKE ESTERS, KETONES, HYDROCARBONS AND GLYCOL ETHERS.